



PLAYING HEIGHT	DIM	HOOPS 21	
		9249	9250
10' (3.05 M)	"A"	8'-8 1/4" (2.65 M)	8'-8 1/4" (2.65 M)
	"B"	1'-9 1/2" (.55 M)	1'-9 1/2" (.55 M)
9' (2.74 M)	"A"	9'-0 3/4" (2.76 M)	9'-0 3/4" (2.76 M)
	"B"	2'-1 3/4" (.65 M)	2'-1 3/4" (.65 M)
8' (2.44 M)	"A"	8'-11" (2.72 M)	8'-11" (2.72 M)
	"B"	2'-0 1/4" (.62 M)	2'-0 1/4" (.62 M)
STORAGE	"D"	9'-6 1/4" (2.90 M)	9'-6 1/4" (2.90 M)

DIMENSIONS IN FEET & INCHES (METERS)

REVISION		
REV.	DATE	BY
-	-	-



Gared Holdings, LLC  
9200 E. 146th St. Noblesville, IN 46060

THIS DOCUMENT CONTAINS TRADE SECRET AND OTHER MATERIALS WHICH ARE PROTECTED BY CONFIDENTIALITY NOTICE AND AGREEMENT AND BY COPYRIGHT. ANY USE OR COPYING OF THIS DOCUMENT EXCEPT AS AUTHORIZED BY GARED HOLDINGS, LLC IS STRICTLY PROHIBITED.

HOOPS 21					
DRAWN	RWP	DATE	04/24/08	MATERIAL	N/A
APPROVED	CONNERLEY	DATE	06/02/08	FINISH	N/A
FILE LOC. Q:\Final Release\Specifications				DWG. NO.	9250
SIZE	SCALE	SHT. NO.	PART NO.	9250	REV
A	NONE	1 OF 1			



## HOOPS 21

### PORTABLE BASKETBALL GOAL

#### **FRAME**

The base frame shall be constructed of 1.5" x 2.5" heavy wall tubing to form a single heavy duty unitized frame. The front mast shall also be constructed of 1.5" x 2.5" heavy wall tubing and connected to the base via integral heavy duty welded hinges. The rear folding brace assembly shall be constructed of 1.5" heavy wall square tubing and connected to the base frame and vertical mast via integral heavy duty welded hinges. The backboard extension assembly shall be constructed of 1.5" heavy wall square tubing.

#### **BALLAST**

Each requires a minimum of 250 lbs ballast (NOT Furnished).

#### **WHEELS**

The upper end of the front mast support shall be equipped with two 3" diameter casters for transport when the unit is folded into the storage position.

#### **FINISH**

Each unit shall be finished in a black powder coat enamel finish.

#### **PADDING**

The front of the vertical mast area shall be padded with a minimum of 2" thick heavy-duty polyurethane foam and covered with a 14-ounce tear resistant, mildew resistant vinyl. All padding shall be attached in a manner for quick replacement. Glue-on type padding will not be considered equal.